STOP

- 1 Do not wash your car for 7 days after installation.
- When washing, keep high pressure spray tip 36" away from PPF.

Why All the Fuss?

The paint protection film installed on your vehicle needs a short period to completely dry before the adhesive can thoroughly bond to the painted surface.

Dry time is determined by weather conditions. This is why your Garware Paint Protection Film dealer has suggested waiting a week before washing your vehicle.

Warning

Although your Garware Paint Protection Film has a durable scratch-resistant coating, you should always use clean and non-abrasive wash mitts and drying materials.

To extend the life of your paint protection film, please review the Care & Maintenance Instructions on the reverse side of this card.

We Appreciate Your Business

Care Tips

Care & Maintenance Instructions:

To ensure that your Garware Paint Protection Film (PPF) remains in excellent condition year after year, please follow these Care & Maintenance Instructions. Failure to adhere to Care & Maintenance Instructions can void your Garware PPF warranty coverage.

- To ensure PPF adhesion, do not wash or wax the vehicle for 7 days after installation.
- To prevent staining, remove bugs, sap, tar, and fallout from the PPF as soon as possible.
- · Do not use solvent-based bug and tar removers.
- · Wash and wax the vehicle as needed.
- · Only wash with soft non-abrasive wash mitts and drying materials.
- When washing, keep high-pressure spray tip 36" away from PPF.
- Non-abrasive wax or sealant application is recommended once every 4 months.
- Do not use polishing compounds, clay bars, or waxes that contain dyes or abrasives.
- To remove PPF see your dealers for proper and safe PPF removal procedures.



Yeah...it's **TOUGH!**



