

#thetrueppf

**GARWARE**  
Paint Protection Film

**PLUS PPF**

**FEATURES**

- Excellent optical clarity
- Excellent stain resistance
- Hydrophobic property
- Excellent chemical resistance
- Easy for installation on curved surfaces

**APPLICATIONS**

- Full body wrap
- Hood
- Bumpers
- Quarter panels
- Painted side mirrors
- Door handle cavity
- Door edges
- Leading hood edge
- Wheel arches
- Rocker panel

PPF installation gel is recommended for proper and easy installation. Recommended installation environment temperatures should be 20° Celsius to 30° Celsius.

**AVAILABILITY**

Garware Paint Protection Film is available at approved distributors, please contact our sales team for roll size, minimum order, warranty and other conditions of sale.



**Corporate Office :**  
Garware House. 50-A, Swami Nityanand Road, Vile Parle (E),  
Mumbai - 400 057 | Tel : +91-22-6698 8000  
Email : info@garwareppf.com

[www.garwareppf.com](http://www.garwareppf.com)

Follow us on

Follow us on

[www.garwareppf.com](http://www.garwareppf.com)

**Corporate Office :**  
Garware House. 50-A, Swami Nityanand Road, Vile Parle (E),  
Mumbai - 400 057 | Tel : +91-22-6698 8000  
Email : info@garwareppf.com



Do's	Don'ts
<ul style="list-style-type: none"> <li>• GARWARE PPF installation should be done in a dust free environment.</li> <li>• Wear lint free &amp; dust free clothes during PPF installation.</li> <li>• Use new cutter blades during installations. This makes the cutting effortless and smooth. 30° angle blade recommended for precise cutting.</li> <li>• Recommended temperature range for PPF installation is 20 to 30°C. Avoid direct sunlight while installation.</li> <li>• Use only recommended gel, solutions and squeeze for installation.</li> <li>• During installation, ensure that there are no air bubbles left between the PPF and painted surface.</li> </ul>	<ul style="list-style-type: none"> <li>• Don't apply PPF on repainted surface.</li> <li>• Don't apply PPF on surface with coatings like Ceramic, Teflon &amp; Wax.</li> <li>• Don't apply GIG on top surface (self healing side) of PPF to avoid gel marks.</li> </ul>

**STORAGE CONDITION**  
The Shelf life of this film is one year when stored in its original packaging at the temperature ranging from 18 to 26°C and Relative Humidity 50 to 60 %.

**PLUS PPF**

#thetrueppf

**GARWARE**  
Paint Protection Film