

#thetrueppf

GARWARE
Paint Protection Film

PREMIUM PPF

FEATURES

- Excellent optical clarity
- Excellent stain resistance
- Self-healing property
- Hydrophobic property
- Anti-yellowing
- Excellent chemical resistance
- Easy for installation on curved surfaces

APPLICATIONS

- Full body wrap
- Hood
- Bumpers
- Quarter panels
- Painted side mirrors
- Door handle cavity
- Door edges
- Leading hood edge
- Wheel arches
- Rocker panel

PPF installation gel is recommended for proper and easy installation. Recommended installation environment temperatures should be 20° Celsius to 30° Celsius.

AVAILABILITY

Garware Paint Protection Film is available at approved distributors, please contact our sales team for roll size, minimum order, warranty and other conditions of sale.



Corporate Office :
Garware House. 50-A, Swami Nityanand Road, Vile Parle (E),
Mumbai - 400 057 | Tel : +91-22-6698 8000
Email : info@garwareppf.com

www.garwareppf.com

Follow us on

Follow us on

www.garwareppf.com

Email : info@garwareppf.com

Mumbai - 400 057 | Tel : +91-22-6698 8000

Corporate Office :
Garware House. 50-A, Swami Nityanand Road, Vile Parle (E),



Don'ts	Do's
<ul style="list-style-type: none"> • Don't apply GIG on top surface (self healing side) of PPF to avoid gel marks. • Don't apply GIG on Teflon & Wax. • Don't apply PPF on surface with coatings like Ceramic. • Don't apply PPF on repainted surface. • Don't apply PPF on placing the PPF on the surface. 	<ul style="list-style-type: none"> • GARWARE PPF installation should be done in a dust free environment. • Wear lint free & dust free clothes during PPF installation. • Use new cutter blades during installations. This makes the cutting effortless and smooth. 30° angle blade recommended for precise cutting. • Recommended temperature range for PPF installation is 20 to 30°C. Avoid direct sunlight while installation. • Use only recommended gel, solutions and squeeze for installation. • During installation, ensure that there are no air bubbles left between the PPF and painted surface.

STORAGE CONDITION
The Shelf life of this film is one year when stored in its original packaging at the temperature ranging from 18 to 26°C and Relative Humidity 50 to 60 %.

PREMIUM PPF

#thetrueppf

GARWARE
Paint Protection Film